

# SAFETY DATA SHEET

STANDARD THINNERS

Page: 1

Compilation date: 15/04/2009

Revision date: 14/12/2011

Revision No: 3

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** STANDARD THINNERS

**Product code:** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Trade Paints (UK) Ltd

Unit 5 The Glade Business Centre

Eastern Avenue

West Thurrock

Essex

RM20 3FH

**Tel:** 0845 838 2225

**Fax:** 01708 680002

**Email:** [sales@tradepaintsuk.co.uk](mailto:sales@tradepaintsuk.co.uk)

### 1.4. Emergency telephone number

**Emergency tel:** 0845 838 2225 (Office Hours Only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F: R11; Xn: R20/21/22; Xi: R36/38; Xn: R48/20; N: R51/53; Xn: R63; Xn: R65; Xn: R68/20/21/22

**Classification under CLP:** Eye Irrit. 2: H319; STOT RE 2: H373; Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Repr. 2: H361f; Skin Irrit. 2: H315; STOT SE 3: H336

**Most important adverse effects:** Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

### 2.2. Label elements

**Label elements under CLP:**

**Hazard statements:** H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 2

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



**Precautionary statements:** P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P273: Avoid release to the environment.

**Label elements under CHIP:**

**Hazard symbols:** Highly flammable.

Harmful.

Dangerous for the environment.



**Risk phrases:** R11: Highly flammable.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 3

**Safety phrases:** S36/37: Wear suitable protective clothing and gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

TOLUENE - REACH registered number(s): 01-2119471310-51

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-625-9	108-88-3	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	10-30%

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46

205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---------------------------------	--	--------

XYLENE - REACH registered number(s): 01-2119488216-32

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	-----------------------------	---	-------

N-HEXANE

203-777-6	110-54-3	F: R11; Xi: R38; Xn: R48/20; Xn: R62; Xn: R65; -: R67; N: R51/53	Flam. Liq. 2: H225; Repr. 2: H361f; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411	1-10%
-----------	----------	--	---	-------

ETHANOL - REACH registered number(s): 01-2119475610-43

200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	--	--------------------	-------

ETHYL METHYL KETONE

201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	--	-------

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 4

ACETONE - REACH registered number(s): 01-2119471330-49

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	---	-------

N-BUTYL ACETATE - REACH registered number(s): 01-2119485493-29

204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED  
LIGHT, DEAROMATIZE

295-434-2	92045-53-9	Xn: R65; F+: R12; Xi: R38; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

PROPAN-2-OL

200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
-----------	---------	-------------------------	--	-------

ISOPROPYL ACETATE

203-561-1	108-21-4	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---------------------------------	---	-------

METHYL ACETATE

201-185-2	79-20-9	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	---	-------

METHANOL - REACH registered number(s): 01-2119433307-44

200-659-6	67-56-1	F: R11; T: R23/24/25; T: R39/23/24/25	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	1-10%
-----------	---------	--	---	-------

ISOBUTANOL - REACH registered number(s): 01-2119484609-23

201-148-0	78-83-1	-: R10; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	-------------------------------------	--	-------

4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	F: R11; Xn: R20; Xi: R36/37; -: R66	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	1-10%
-----------	----------	-------------------------------------	--	-------

PROPYL ACETATE

203-686-1	109-60-4	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---------------------------------	---	-------

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 5

### BUTAN-1-OL

200-751-6	71-36-3	-: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	<1%
-----------	---------	--	---	-----

### PROPAN-1-OL

200-746-9	71-23-8	F: R11; Xi: R41; -: R67	Flam. Liq. 2: H225; Eye Dam. 1: H318; STOT SE 3: H336	<1%
-----------	---------	-------------------------	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues

**Ingestion:** Wash out mouth with water. If patient is conscious, give water to drink. If patient feels unwell, seek medical advice. DO NOT INDUCE VOMITING.

**Inhalation:** Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 6

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Original container stored in a dry and cool place.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 7

### Hazardous ingredients:

#### TOLUENE

##### Workplace exposure limits:

##### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	-	-

#### ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

#### XYLENE

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

#### N-HEXANE

UK	72 mg/m3	No List	-	-
----	----------	---------	---	---

#### ETHANOL

UK	1920 mg/m3	-	-	-
----	------------	---	---	---

#### ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	-	-
----	-----------	-----------	---	---

#### ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

#### N-BUTYL ACETATE

UK	724	966	-	-
----	-----	-----	---	---

#### PROPAN-2-OL

UK	999 mg/m3	1250 mg/m3	-	-
----	-----------	------------	---	---

#### ISOPROPYL ACETATE

UK	no std	849 mg/m3	-	-
----	--------	-----------	---	---

#### METHYL ACETATE

UK	616 mg/m3	770 mg/m3	-	-
----	-----------	-----------	---	---

#### METHANOL

UK	266 mg/m3	333 mg/m3	-	-
----	-----------	-----------	---	---

#### ISOBUTANOL

UK	154 mg/m3	231 mg/m3	-	-
----	-----------	-----------	---	---

#### 4-METHYLPENTAN-2-ONE

UK	208 mg/m3	416 mg/m3	-	-
----	-----------	-----------	---	---

#### PROPYL ACETATE

UK	849 mg/m3	1060 mg/m3	-	-
----	-----------	------------	---	---

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 8

### BUTAN-1-OL

UK	-	154 mg/m3	-	-
----	---	-----------	---	---

### PROPAN-1-OL

UK	500 mg/m3	625 mg/m3	-	-
----	-----------	-----------	---	---

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves, change regularly to avoid permeation problems. Ensure gloves are manufactured/tested in accordance with BS EN 374.

**Eye protection:** Safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Off-white

**Odour:** Perceptible odour

**Evaporation rate:** Moderate

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Slightly soluble

**Also soluble in:** Most organic solvents.

**Boiling point/range°C:** 55-155

**upper:** 12.8

**Autoflammability°C:** >203

**pH:** 7.71

**Flammability limits %: lower:** 1.1

**Flash point°C:** <21

**Relative density:** 0.831-0.881

### 9.2. Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]



# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 9

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous: calculated
Irritation	OPT DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** Not applicable.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This substance is not identified as a PBT substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 10

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

#### 14.1. UN number

**UN number:** UN1263

#### 14.2. UN proper shipping name

**Shipping name:** PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

**Transport class:** 3

#### 14.4. Packing group

**Packing group:** II

#### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

#### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 2

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

#### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and 3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 11

H225: Highly flammable liquid and vapour.  
H226: Flammable liquid and vapour.  
H301: Toxic if swallowed.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters  
airways. H311: Toxic in contact with skin.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation. H336:  
May cause drowsiness or dizziness.  
H340: May cause genetic defects <state route of exposure if it is conclusively proven that  
no other routes of exposure cause the hazard>.  
H350: May cause cancer <state route of exposure if it is conclusively proven that no other  
routes of exposure cause the hazard>.  
H361d: Suspected of damaging the unborn child.  
H361f: Suspected of damaging fertility.  
H370: Causes damage to organs <or state all organs affected, if known> <state route of  
exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H373: May cause damage to organs <or state all organs affected, if known> through  
prolonged or repeated exposure <state route of exposure if it is conclusively proven that  
no other routes of exposure cause the hazard>.  
H411: Toxic to aquatic life with long lasting effects.  
R10: Flammable.  
R11: Highly flammable.  
R12: Extremely flammable.  
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R20/21: Harmful by inhalation and in contact with skin.  
R20: Harmful by inhalation.  
R22: Harmful if swallowed.  
R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.  
R36/37: Irritating to eyes and respiratory system.  
R36/38: Irritating to eyes and skin.  
R36: Irritating to eyes.  
R37/38: Irritating to respiratory system and skin.  
R38: Irritating to skin.  
R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in

[cont...]

# SAFETY DATA SHEET

## STANDARD THINNERS

Page: 12

contact with skin and if swallowed.

R41: Risk of serious damage to eyes.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

