



Concrete Sealer

PRODUCT DATA

Description

Concrete sealer is based on a thermoplastic acrylic resin to give flexibility and UV resistance. It is suitable for application to seal concrete floors and block paving driveways and will provide a hard wearing, water, petrol and oil resistant.

Important Note: Some stone surfaces can change colour when this type of product is applied (e.g. Indian Sandstone turns brown). If in doubt, please carry out a small test application first.

Area of use

Interior and exterior.

Substrates

Concrete/Stone/Block floors and driveways

Packing

5 litres

Physical Constants

Colour:	Clear
Finish:	Gloss
Volume solids:	30%
Theoretical spreading rate:	16 sq. metres per litre
Flash point:	23°C
Specific gravity:	0.9
Dry to touch:	6 hours (20°C)
Overcoating time:	16 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	Xylene
Cleaning of tools:	Xylene

Surface condition

The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.