

PRODUCT DATASHEET

SCAFFOLD MARKING PAINT

INTENDED USE

METAL FINISHING

A half hour (30 minutes) dry high gloss brush and spray enamel for the identification & ownership of scaffold towers and equipment. It is used wherever there is a need for general purpose finish to dry rapidly.

It may also be used 'direct to metal' without a primer for items that have no need for corrosion protection nor require a primer to fill surface imperfections and will only be used internally. Typical uses without a primer are small cast items and metal shelving.

SUITABLE SUBSTRATES AND PREPARATION

Surfaces must be dry sound and free from dirt, dust and grease.

For spray application prime with QD Zinc Phosphate Primer or similar. Previously painted glossy surfaces should be lightly abraded prior to application to promote adhesion. Any non-ferrous metals must be pre-treated with 2K Wash Etch Primer, or 1 Pack Etch Primer.

AVAILABILITY

Gloss finish available in a large range of popular colours stocked in 5 litre tins. An extensive range of BS, RAL and other colours are available from the mixing Scheme. Semi-gloss and Semi-matt finishes are also available to order.

PRODUCT INFORMATION

(TYPICAL FIGURES)

Composition	Based on a short oil alkyd resin, pigmented with suitably selected pigments.
Volume Solids	40-43%
Weight Solids	46-60%
VOC content	495-530 g/litre
Typical film thickness	30 microns dry or 75 microns wet film thickness
Theoretical coverage	13 sq metres/litre at 75 microns wet film thickness
Dry heat resistance	80 C
Flash Point	Within the range 21-31 C

**SAFETY
PRECAUTIONS**

Refer to Trade Paints Safety Data Sheet

LIMITATIONS

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied however, since the conditions of use are beyond our control. This data sheet does not constitute a specification.

A Painting Guide can be accessed via our website which provides additional information on paint and painting and definitions of terminology.

In case of doubt as to the suitability of the product please consult our Technical Department. If you are advised that the paint can be used in a manner not specified on this datasheet our Technical Department will confirm this to you in writing. Do not use paint prior to receiving this confirmation.

References to other primers, topcoats, cleaners and thinners are to the Trade Paints Product of that name only.

This data sheet supercedes all previous issues.

REFERENCES

Amended date: November 27, 2012

Reference and number: QD- 7