



## PRODUCT DATA SHEET

### UPAINTPVC ALL-IN-ONE UPVC PAINT

---

Upaintpvc All-In-One UPVC and plastic paint is a fast drying easy to apply all surface coating. Durable and U.V weather resistant, Upaintpvc shows excellent colour stability and film flexibility, designed to recolour, regenerate, and retouch damaged, tired, worn UPVC, plastic and plastisol.

Upaintpvc is primarily designed and Ideal for :

- UPVC Doors
- UPVC Windows & Frames
- UPVC Conservatories
- UPVC & Plastic Fascias
- Plastisol Exterior Cladding
- Plastic Downpipes & Gutters
- Plastic Furniture

Do not use on areas exposed to extreme heat such, or constant high humidity environments. Do not use in continuous water immersion such as swimming pools, hot tubs, ponds, or saunas.

Because of its special properties Upaintpvc is undoubtedly one of the best resurfacing maintenance coatings on the market. Ideal for brush and roller and spray application.

With Upaintpvc you can transform your home for relatively little expense and time!

Our proven formula recolours, regenerates, tired, damaged and discoloured UPVC and plastic surfaces – saving you hundreds of pounds on the cost of replacement.

Upaintpvc is available in a semi matt finish.



## **Usage**

Before applying carefully read the instructions on the container and use according to the manufacturer's recommendations.

## **Preparation**

To secure lasting adhesion to the subsequent product all surfaces shall be clean, dry and free from any contamination.

Clean the surface in preparation for sanding.

Thoroughly abrade the surface with a suitable P600 abrasive sandpaper.

To ensure a clean, tidy finish round the edges and the fittings, we recommend applying masking tape to areas that do not require resurfacing and renovating.

## **Application**

Apply at temperatures between 10-25°C in a well ventilated room.

Stir thoroughly.

Use a fine quality, fine bristle brush. Brush in one direction only for a smooth surface and feather the edges as you paint to avoid a hard line between painted areas. Avoid excessive brushing to ensure an even coat and smooth finish. Brush around the edges and the fittings.

## **Coverage**

Up to 5.5m<sup>2</sup> per litre. Depending on application and rate of application.



## **Cleaning and Thinning**

We recommend using Xylene Thinner. Do not empty into drains or water courses.

## **Availability**

Available in 2.5 litre containers in BS381c, BS4800 and Ral colours.

<b>Substrate temperature</b>	<b>20°C</b>
Surface (touch) dry	30-45 Minutes
Hard Dry	24 Hours
Minimum Overcoating	4 Hours

## **Storage and Shelf Life**

Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Volatile Organic Compounds (VOC) – 500g per litre

Shelf life at 20°C – 48 months

Flash Point – 23-32°F (25 °C)

## **Health and Safety**

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.